


APL3700T – 15” Touch-Panel PC



TouchPanel Operation



15-inch TFT Color LCD
Touch-Panel Computer

APL3700T

DC 24V	15-inch
AC100/240V	
XGA	

CPU: Intel® Celeron® M 1.86GHz or Intel® Core™ Duo 2.0GHz



Windows®
All-in-one model
Factory Alert
CF Card
SSD
RAID

Features:

- 15" (XGA 1024 x 768) TFT touch-panel computer
- Intel® Core™ Duo 2.0GHz or Intel® Celeron® M 1.86GHz CPU
- 250 GB Hard Drive, Solid State Drive or bootable Compact Flash
- DVD-RW standard
- Reliability, Availability, Serviceability (RAS) Remote Health Monitor
- IP65f, NEMA 4/4x/12 Rated
- SSD (Solid State Drive) for Reliability and

faster data access

- Data protection – RAID1 hard disk option
- RoHS directive-conforming
- UL 1604, Class I, Div 2, Groups A, B, C, D

Open HMI WinGP Option

- Use PC as on-demand touch-screen HMI
- Allows third-party applications to run concurrently
 - SPC, vision, SCADA, MRP
- Expands PC hardware and data connectivity options

Performance Specifications

	Performance	Standard
Base Model	APL3700-TA-CD2G APL3700-TD-CD2G	APL3700-TA-CM18 APL3700-TD-CM18
CPU	Intel® Core™ Duo 2.0GHz	Intel® Celeron® M 1.8GHz
Supported OS	Windows® XP Pro / XP ML	Windows® XP Pro / XP ML
Standard Memory	1GB/ 2GB/ 4GB	
Maximum Memory	4GB (DIMM socket x 2)	
Graphics Display Resolution	XGA (1024 x 768 pixels)	
Video Memory	Max 64MB (UMA type)	
Display Type and Size	TFT Color LCD (15-inch)	
Display Colors	262,144 Colors	
Display Area	W306.2mm [12.06 in.] x H230.1mm [9.06in.]	
Touch Screen	Resistive Film (Analog) Touch Screen, 1024 x 1024	
Serial	COM1: RS-232C, D-sub 9 pin (plug) (RI/+5V switchable, RS-422/RS-485 switchable) COM2: RS-232C, D-sub 9 pin (plug) (RI/+5V switchable) COM3: RS-232C, D-sub 9 pin (plug) COM4: RS-232C, D-sub 9 pin (plug)	
LAN	Rear 2 ports. RJ-45 type modular jack connector (8 pins). LAN1: auto change to 10BASE-T/100BASE-TX/1000BASE-T LAN2: auto change to 10BASE-T/100BASE-TX	
USB	USB 2.0-compatible rear 4 ports, front 1 port. Disable/enable selectable	
Sound	Speaker out (3.5mm mini-pin jack connector)	
RAS (Remote Health Monitor)	Rear RAS connector 9-pin socket	
Disk	250 GB hard drive, 16-128 GB Solid State Drive. . SATA interface. IDE interface: Master: 8 GB CF card I/F. Slave: DVD-RW 1 slot	
PCI	PCI x 2 or PCI x 4; first 2 slots are:174.63 [6.88 in.] x 106.68 [4.20 in.] mm; Slots 3 and 4 are: 250 [9.84 in.] x 106.68 [4.20 in.] mm	

General Specifications

Input Voltage	AC100 / 240V (Rated voltage AC85 to 264V; 50/60Hz)	DC24V (Rated voltage DC19.2 to 28.8V)
Power Consumption	145VA or less	145W or less
Allowable Voltage Drop	1 cycle or less (Voltage drop interval must be 1s or more.)*1	5ms or less
Voltage Endurance	AC1500V 20mA for 1 minute (between charging and FG terminals)	AC1000V 20mA for 1 minute (between charging and FG terminals)
Insulation Resistance	DC500V 10MΩ(min.) (between charging and FG terminals)	
Certifications	UL 508; CSA-C22.2 No. 142-M1987; CE Marking EN61000-6-2, EN55011 Class A, EN60950-1 (Only AC model), 47 CFR Part 15 Class A, UL 1604, Class I, Div 2, Groups A, B, C, D	
Temperature	0 to 50°C (32 to 122°F) without HDD; 5 to 50°C (41 to 122°F) with HDD; Storage Temperature: -20 to +60°C (-4 to 140°F)	
Humidity - Ambient/Storage	10 to 90% RH [Not condensing, wet bulb temperature: 39°C (122°F) or less; with HDD: 29°C (84.2°F) or less].	
Corrosive Gas	Free of corrosive gases	
Noise Immunity	Noise Voltage: 1500Vp-p, Pulse Duration: 50ns, 500ns, 1µs Rise Time: 1ns (via noise simulator)	Noise Voltage: 1000Vp-p, Pulse Duration: 1µs Rise Time: 1ns (via noise simulator)
Cooling Method	Forced air cooling by system fan and CPU fan	
Electrostatic Discharge Immunity	6kV (complies with EN 61000-4-2 Level 3)	
Vibration Resistance	IEC61131-2 compliant, With HDD: 10 to 57Hz half-amplitude 0.075mm, 57 to 150Hz constant-accelerated velocity 9.8m/s ² . X, Y, Z directions for 10 cycle (100 minute) Without HDD: 5 to 9Hz half-amplitude 3.5mm, 9 to 150Hz constant-accelerated velocity 9.8m/s ² . X, Y, Z directions for 10 cycle (100 minute)	
Shock during operation	EN/IEC 60068-2-2 compliant, 147m/Sec, 11msec (Approx. 15G), 3 shocks to 3 direction/ axis	
Rating	Equivalent to IP65f, NEMA 4/4x/12 (only when not using front USB)*2	
Weight With DVD-RW	2 slots: Approx. 13.45kg [29.6lb] 4 slots: Approx. 14.45kg [31.8lb]	
External Dimensions With DVD-RW	2 slots: W425mm [16.73in.] x H325mm [12.8in.] x D203.0mm [7.98in.] 4 slots: W425mm [16.73in.] x H325mm [12.8in.] x D255.0mm [10.03 in.]	
Warranty	Two-year standard (maximum 4 years)	


*1 Depending on the combined total of the expansion slot power supply and external load power values, the allowable voltage drop may be 20ms or less. *2 Meets IP65f testing requirements. Operation is not, however, guaranteed in every environment.

APL3700T - External Dimensions


Dimensions shown with installation fasteners attached
APL3700T (2-slot) **APL3700T (4-slot)**

Unit: mm [in]


Unit: mm [in]




Front




Front



Top




Top



Side


Units are shown without DVD; add 37.5mm [1.47"] to the depth (D).



Side

APL3700T - Cutout Dimensions

Unit: mm [in]





* Compatible with Xycom 4615T

* To be compatible with Xycom 4715T, adapter plate is required (order number: 145053)

Optional Items

Product Name		Part Number
DIMM Memory Module	512 MB	CA7-DDR2-512MB
	1 GB	CA7-DDR2-1GB
	2 GB	CA7-DDR2-2GB
HDD Unit *1	250 GB	APL3000-HD250
CF Card*1	512MB	CA3-CFCALL/512MB-01
	1GB	CA6-CFCALL/1GB-01
	2GB	CA8-CFCALL/2GB-01
	8GB	144766
RAID Kit		RAID-KIT-01
USB Front Cable	1m	CA5-USBEXT-01
USB Cable	5m	FP-US00
RS-232C Cable	5m	FP61V-IS00-O
DVI-D Cable	5m	FP-DV01-50
Analog RGB Cable *2	4.5m	FP-CV02-45
RGB Converter Cable	5m	CA7-CBLCVRGB-01
DVI-D/RGB Branch Cable	15cm	CA7-CBLCVDVI-D/RGB-01
External Floppy		9000-USBF
Backlight (2 pieces/set for 1 unit)		CA7-BLU15-01
Installation Fasteners		APL-ATFB-01
Screen Protection Sheets (5-sheet set)		CA7-DFS12-01
Adapter Plate*3		145053

*1 Not installed with operating system. *2 When using the DVI-D/RGB branch cable.
 *3 APL3700T cutout adapter for 4715T cutout.



Caution: Before operating any of these products, please be sure to read all related manuals thoroughly.
 - All product names used in this document are trademarks or registered trademarks of their respective companies.
 - All information contained in this document is subject to change without notice.

APL3000 Cutout Compatibility

If you have :	This will fit the same cutout :	Notes:
4612T, 3612T, 3510(T), 3512T, 3310T, 3410T, 9460(T), 9462(T), 9410T, 9412T, 3412T, 3312T	APL3600T	
4612KPM(T), 3612KPM(T), 3510KP(T), 3512KP(T), 9460KP, 9462KP, 9410KP(T), 3410KP(T), 3310KP(T), 9412KP(T), 3412KP(T), 3312KP(T)	APL3600K	*1
4615T, 3615T	APL3700T	
4715T, 3715T, 3515(T), 3535T, 9465(T)	APL3700T + Adapter plate	Adapter plate : 145053
4715KPM(T), 4615KPM(T), 3615KPM(T), 3715KPM(T), 3515KPM(T), 3512KPM(T), 3535KPM(T), 9465KPM(T)	APL3700K	

*1 When you Migrate from 3612KPM(T)/4612KPM(T) to APL3600K requires removing attachment plate screwed on APL. More details see APL3000 series Hardware Manual.
 (The original cutout size with spacers is to keep compatibilities with PL3700, FP3710, AGP3750 and PS3710/11)

Ordering Information

APL3700-T	-	-	-	-	-	-	-	-M-	-	-	-
Power supply											
A..... AC 100-240V											
D..... DC 24V											
CPU											
CM18..... CeleronM440 1.86GHz											
CD2G.....CoreDuo 2.0GHz											
Expansion slots											
2P.....PCI x 2 slots											
4P.....PCI x 4 slots											
Memory (DRAM)											
1G.....1GB											
2G.....2GB											
4G.....4GB											
Operating System											
(RAID and secondary Storage option is not supported with SSD option)											
XM250.....250GB HDD w/XP ML											
XPC08.....8GB CF w/XP Pro*											
XM16S.....16GB SSD w/XP ML											
XM16SA...16GB SSD w/XP ML											
XM32SA...32GB SSD w/XP ML											
XM64SA....64GB SSD w/XP ML											
XM128SA..128GB SSD w/XP ML											
Secondary Storage											
Blank.....No Secondary Storage											
NO250.....250GB HDD											
NO16SA....16GB SSD											
NO32SA....32GB SSD											
NO64SA....64GB SSD											
NO128SA...128GB SSD											
RAID											
Blank.....No RAID options											
R.....RAID											
Open HMI (WinGP)											
Blank.....No Open HMI software included											
WG.....WinGP installed											

*The languages included with this version of Windows XP Pro are English, French, Spanish, Brazilian Portuguese, Japanese, Simplified and Traditional Chinese.

Pro-face America
Phone: 734.429.4971
Fax: 734.429.1010
www.profaceamerica.com

Customer Service Hotline: 734.944.0482

For more information
ACCESS www.profaceamerica.com

